



TECHNICAL INFORMATION SHEET 14

## Cleaning Tips for Aristech Acrylics LLC Acrylic Surfaced Products

AristechAcrylics LLC Continuous Cast Acrylic Sheet is manufactured in different formulations for a variety of demanding applications.

---

To properly clean an Aristech Acrylics LLC acrylic-surfaced product, it is recommended wiping the surface with a soft damp cloth (or sponge) using household soap or liquid detergent. Stubborn dirt or stains may be removed by using Spic & Span adequately dissolved in water.

DO NOT use any cleaning products containing abrasives or solvents since these could dull the brilliant surface. Products like Bon-Ami, Comet, Ajax, or Lysol are not recommended. Harsh chemicals should never be used on acrylic surfaces.

The procedure to remove a light surface scratch or burnish mark is quite simple. Apply paste wax or automobile rubbing compound to the scratch and then mildly buff the area. This will return the original luster and shine to the marred acrylic surface. Should a deep scratch or more serious damage be encountered, please consult the product manufacturer or Aristech Acrylics LLC Technical Service Department for repair instructions

Aristech Acrylics LLC acrylic's long lasting beauty, when properly maintained, will prevail indefinitely. Mildew should never be a worry because acrylic is nonporous. Acrylic surfaced products are made from a single sheet of material; this results in no grout to scrub, no corners to collect dirt, and no seams to clean. The bottom line is, very little time will be needed to maintain an Aristech Acrylics LLC acrylic surfaced product.

*For cautions and other information relating to handling of an exposure to this product, please see the applicable material safety data sheet published by Aristech Acrylics LLC.*

These instructions are based upon experience with Aristech Acrylics LLC products only. Experience with products of other manufacturers is specifically disclaimed. For most uses, check for local code approval and test for application suitability. These procedures, techniques and suggested materials should only be used by personnel who are properly trained in the safe handling of the chemicals and the equipment with which they are working. Avoid aromatic solvents, clean with mild soap and water, avoid abrasives. These suggestions are based on information believed to be reliable, however, Aristech Acrylics LLC makes no warranty, guarantee, or representation and assumes no obligations or liability as to the absolute correctness or sufficiency of any of the foregoing, or that additional or other measures may not be required under particular conditions or circumstances.



7350 Empire Drive • Florence, KY 41042  
(859) 283-1501 • Toll Free 800-354-9858  
[www.aristechacrylics.com](http://www.aristechacrylics.com)

March 2007